



Utilizzare solo / Use only:
162.604.20 Ø8
162.604.21 Ø10

IMPUGNATURA M4 M4 TRIGGER HANDLE

Pressione di esercizio max.: 20 bar
Peso: 160 g

Materiali: ottone - acciaio inox - materiali plastici ad alta resistenza tenute in NBR

Impiego: completa di filtro. Per spruzzare insetticidi, diserbanti, emulsioni oleose, lubrificanti.

Max. operating pressure: 20 bar (290 psi)
Weight: 160 g (5.6 oz)

Materials: brass - s.steel - high resistance plastic materials
Buna N gaskets

Use: fitted with strainer. Insecticides, weed control, oil and lubricant spraying.

COME SI ORDINA / HOW TO ORDER

CODICE code	ATTACCO connection		KIT RICAMBIO spare parts kit
4.802.14	G1/2M. - Ø12x19F. maschio 1/2"BSPM. - Ø12x19F. male	10	4.302.2
4.802.15	G1/2M. - G1/4F. 1/2"BSPM. - 1/4"BSPF.	10	4.302.2



30.1509.5

Ø12x19F. - G1/2M.
Ø12x19F. - 1/2"BSPM.

Materiali: ottone
Materials: brass



VALVOLA M23 M23 TRIGGER VALVE

Versioni: con attacco G1/2F.
con attacco G1/2M.

Pressione di esercizio max: 50 bar
Peso: G1/2M. G1/2F. 340 g - G1/2F. G1/2F. 300 g
Portata max.: 70 l/min

Materiali: alluminio con trattamento al nichel chimico - sede e pistone di tenuta in acciaio inox - ottone - tenute in FPM - materiali plastici ad alta resistenza.

Impiego: valvola on/off. In agricoltura come impugnatura per lance. Impieghi industriali per lubrificazione a pressione. Protezione per la mano dell'operatore.

Models: with 1/2"BSPF. connection
with 1/2"BSPM. connection

Max. operating pressure: 50 bar (725 psi)
Weight: 1/2"BSPM. 1/2"BSPF. 340 g (12 oz)
1/2"BSPF. 1/2"BSPF. 300 g (10.6 oz)
Max. capacity: 70 l/min (18.5 USGal/min)

Materials: Electroless nickel plated aluminum body - stainless steel seat and shut off piston - brass - FKM gaskets - high resistance plastic materials.

Use: On/off valve. For agricultural and industrial use like oiling and greasing. Hand shield.

COME SI ORDINA / HOW TO ORDER

CODICE code	ATTACCO connection		KIT RICAMBIO spare parts kit
23.208.84	G1/2M. - G1/2F. 1/2"BSPM. - 1/2"BSPF.	10	23.302.26
23.1903.11	G1/2F. - G1/2F. 1/2"BSPF. - 1/2"BSPF.	10	23.302.26



VALVOLE M29 - M30 M29 - M30 TRIGGER VALVES

Versioni standard:

M29: entrata G1/2M. o G1/2F. - guarnizioni in FPM - sede e pistone di tenuta in acciaio inox

M30: entrata G1/2M. o G1/2F. - guarnizioni in NBR - sede in materiale plastico ad alta resistenza - sfera di tenuta in acciaio inox.

Pressione di esercizio max: M29 50 bar - M30 20 bar
Peso: 200 g
Portata max.: 70 l/min

Materiali: materiali plastici ad alta resistenza - componenti in ottone e acciaio inox.

Impiego: valvole on/off. Eccellente resistenza ai prodotti chimici ed alla pressione. Impiego agricolo (diserbo localizzato) e industriale (nebulizzazione soluzioni oleose e lavaggio) con ottimo comfort per l'operatore.

Standard models:

M29: 1/2"BSPM. or 1/2"BSPF. inlet - FKM gaskets - stainless steel seat and shut off piston.

M30: 1/2"BSPM. or 1/2"BSPF. inlet - Buna N gaskets - high resistance plastic seat - stainless steel shut off ball.

Max. operating pressure: M29: 50 bar (725 psi)
M30: 20 bar (290 psi)
Weight: 200 g (0.45 lb)
Max. capacity: 70 l/min (18.5 USGal/min)

Materials: high resistance plastic materials - brass and stainless steel parts.

Use: on/off trigger with excellent corrosion and pressure resistance. Suitable for spot spraying in agriculture and for industrial applications (lubrication, nebulization and washing). Comfortable palm fitting.

COME SI ORDINA / HOW TO ORDER

CODICE code	ATTACCO connection		KIT RICAMBIO spare parts kit
29.1903.7	G1/2M. - G1/2F.	10	29.302.24
30.1903.6	1/2"BSPM. - 1/2"BSPF.	10	30.302.25
29.1903.9	G1/2F. - G1/2F.	10	29.302.24
30.1903.8	1/2"BSPF. - 1/2"BSPF.	10	30.302.25



UGELLI
TIPS PAGE 83



PAGE 20