



### Standard Features:

- Compact, reliable PTO pump capable of 150 to 530 gpm with corresponding pressures of 161 to 131 psi using 29 to 59 hp
- Available with heavy duty two wheeled trailer or galvanized three point mount
- Designed with industry leading oil lubricated step up gearbox (no belts or pulleys) with shafts supported by widely spaced bearings
- Easily replaceable packing gland type water seal

### Options:

- 4" female thread discharge priming valve
- Hand primer
- Fluid filled pressure gauge
- Short suction adapter with 4" female pipe thread
- #6 heavy duty 1 $\frac{3}{8}$  six spline PTO shaft.



### Configurations:

- Bare Pump:** Pump only with weld-on companion flanges, gaskets, nuts and bolts
- Pump, Cart & Shaft:** Same as bare pump, but mounted on two-wheeled cart & PTO drive shaft
- Fully Fitted:** Same as pump, cart & shaft plus hand primer, check valve, pressure gauge and suction fittings

### Specifications:

- **Suction (A,B):** 80mm DIN Flange
- **Discharge (A,B):** 65mm DIN Flange
- **Discharge/Suction (C):** 4" NPTF
- **Discharge Position:** Horizontal, Right Facing (When Standing Behind The Suction End)
- **Length:** 65 Inches
- **Width:** 48 Inches
- **Height:** 40 Inches
- **Weight (Unfitted):** 270 lbs.
- **Weight (Fitted):** 330 lbs.



The performance information contained herein is based on ideal conditions. Actual performance is affected by, but not limited to, location, operating conditions (Temperature, humidity & altitude) and human judgement. Idrofoglia USA reserves the right to change product specifications, designs, pricing and standard equipment without notice and without incurring obligation.