

Maximum suggested horsepower



200 HP - 146 KW



www.celli-usa.com

Toll Free: 1-877-591-4790

ENERGY

ENERGY														Nr.
	IN	CM	IN	CM		HP / KW	LBS	KG	LBS	KG	LBS	KG	LBS	
250	100	255	98	250	80/59	2315	1050	2315	1050	1050	1200	2381	1080	20
300	120	305	118	300	100/73	2579	1170	2579	1170	1170	1340	2645	1200	24
350	140	355	138	350	130/95	2844	1290	2844	1290	1290	1480	2910	1320	28
400	159	405	157	400	150/109	3018	1410	3018	1410	1410	1620	3175	1440	32

Total width	Weight with spikes roller	Weight with spiral roller	Min. suggested horsepower
Working width	Weight with packer roller	N° of blades	Weight with cage roller

FIXED POWER HARROW



POINTS OF STRENGTH:

- The oil sealing system with labyrinth grooved section and double lip seal with steel casing.
- The effective tines quick release system (on request) simple and reliable that allows to dramatically cut the time for maintenance.
- The forged steel bottom housing for a long life of the machine and for working in the most difficult conditions.
- The effective stone protection system (on request) to safeguard the rotors, to limit their wearing, to avoid their blocking when working.
- The reduced overall size of the machine featuring the centre of gravity very close to the tractor

TECHNICAL SPECIFICATIONS

- maximum horse power: 200 HP (146 KW)
- 2 speed gearbox for 1000 rpm PTO
- 3 point hitch cat.2
- swinging lower linkages
- counter-plates for tines locking
- rear roller adjustment by pins
- rear levelling bar adjustment by threaded bar
- tines 120x15x300 mm: working depth about 30 cm
- movable side plates
- drive shaft with shear bolt
- removable safety protections