













Maximum suggested horsepower ► **45 HP**

	Total width
	Working width
	Side-shift
	Min. suggested horsepower
	Weight
	Number of blades

F/BA						
	in	in	in-in	HP	lbs	Nr.
105	47	41	20 - 20	25	485	30
125	55	49	24 - 24	30	578	36
145	63	57	28 - 28	35	562	42
165	71	65	32 - 32	40	595	48



www.cellli-usa.com
Toll Free: 1-877-591-4790

F/BA

The rotary tiller **F/BA** combine a modern design to high quality technical features, generally reserved to bigger models.

It is worth noting that the box section frame is made of a welded double plate to guarantee adequate resistance, the transmission gears are oversized, the rear cover is well shaped to get an ideal finishing and levelling of the soil.



FIXED ROTARY TILLER
suitable for small size tractors

TECHNICAL SPECIFICATIONS

- Maximum horsepower 45 HP
- Rotor speed: 221 rpm (for 540 rpm PTO)
- Chain side drive
- 3 point hitch cat. 3
- L-shaped blades: 60x6 mm (6 blades each flange, side blades leaning inwards)
- Working depth about 7"
- Side-skids
- Food stand
- Drive shaft without safety device
- Removable safety protections

OPTIONAL ACCESSORIES

- 4 speed gearbox for 540 rpm PTO
- C-shaped blades
- Side blades leaning inwards
- Set of 2 front wheels
- Extended upper and lower 3 point hitch
- Drive shaft with shear bolt
- Drive shaft with clutch

