

PRO-C® & PCC

Number of Stations: **4 - 16, 6 and 12**
 Type: **Modular & Fixed**

FEATURES

- Number of stations:
 - Pro-C: 4-16
 - PCC: 6 & 12
 - Type:
 - Pro-C: Modular
 - PCC: Fixed
 - Enclosures: Indoor and outdoor plastic
 - Independent irrigation programs: 3
 - Independent lighting programs: 3
 - Start times per program: 4
 - Max. station run time: 6 hours
 - Solar Sync® Delay feature allows adjustments to be postponed for up to 99 days
 - Cycle and Soak feature built in: reduces runoff
 - Added knockouts for additional flexibility
 - Non-volatile memory
 - Rain sensor bypass
 - One touch manual start and advance
 - Warranty period: 2 years
- ▶ Built in Solar Sync
 - ▶ Easy Retrieve™ memory
 - ▶ QuickCheck™
 - ▶ Automatic short circuit protection
 - ▶ Seasonal Adjustment: Global or automatic updates with Solar Sync
 - ▶ Delay between stations
 - ▶ Sensor programmability
 - ▶ Non-Water Days

ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Operating temperature: -18° C to 60° C

APPROVALS

- CE, UL, cUL, C-tick, FCC
- ▶ = *Advanced Feature descriptions on page 106*



Plastic Indoor
 Height: 20.9 cm
 Width: 24.3 cm
 Depth: 9.7 cm



Plastic Outdoor
 Height: 22.5 cm
 Width: 25 cm
 Depth: 11 cm



PCM-300 and PCM-900 Expansion Modules
 These modules are compatible with the new Pro-C 400 series.

CONTROLLERS

PRO-C SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4							
1	Models	2	Transformer	3	Indoor/Outdoor	4	Options
	PC-4 = 4-station base module controller		00 = 120 VAC 01 = 230 VAC		(blank) = Outdoor Model (internal transformer) i = Indoor Model (plug-in transformer)		(blank) = No option E = 230 VAC with European Connections A = 230 VAC with Australian Connections (outdoor models have internal transformer with cord)
	PCC-6 = 6-station						
	PCC-12 = 12-station						

PC-SERIES STATION EXPANSION	
Modules	Description
PCM-300	3-station plug-in module: Use to increase station count from 4 to 7, 7 to 10, and 10 to 13
PCM-900	9-station plug-in module: Use to increase station count from 7 to 16

Examples:
PC-400 = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet
PCC-601i - E = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet
PCC-1200 = Fixed 12-station outdoor controller, Internal 120 VAC transformer, and plastic cabinet