

PSR

PUMP START RELAY

Type: **Accessory**

FEATURES

- Choice of three models sized accordingly to fit your particular application
- NEMA 3R rated locking plastic enclosure rated for outdoor use, weather resistance and security
- 24 VAC flying leads make it quick and easy to wire to controller
- The PSR-22 meets demanding electrical requirements for UL approval, and the PSR-52/-53 contains UL-approved relays
- Warranty period: 2 Years



Pump Start Relay

Height: 17 cm
Width: 19 cm
Depth: 12 cm

PUMP START RELAY

Model	Description
PSR-22	Double pole/single throw pump start relay for 120 VAC pumps up to 1.5 kW or 230 VAC pumps up to 2.2 kW
PSR-52	Double pole/single throw pump start relay for 120 VAC pumps up to 2.2 kW or 230 VAC pumps up to 5.6 kW
PSR-53	Triple pole/single throw pump start relay for 120 VAC pumps up to 2.2 kW, 230 VAC pumps up to 5.6 kW, or 230 VAC pumps up to 7.5 kW (3 phase)

PUMP START RELAY ELECTRICAL SPECIFICATIONS

Model	Single Phase		3 Phase	Max. Full Load AMPS	Max. Resistive AMPS	Coil VA				Coil VA			
	kW AT 120 VAC	kW AT 230 VAC	kW AT 230 VAC			INRUSH		AMPS		HOLDING		AMPS	
						50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz
PSR-22	1.5*	2.2*	N/A	30	40	33	30	1.38	1.25	8	6.5	0.33	0.27
PSR-52	2.2	5.6	N/A	40	50	65	60	2.71	2.50	7.5	5	0.31	0.21
PSR-53	2.2	5.6	7.5	40	50	65	60	2.71	2.50	7.5	5	0.31	0.21

Note:
* Approximate power

PSRB

PUMP START RELAY BOOSTER

FEATURES

- Solves long distance pump start relay power challenges
- Suitable for conventional or ICD decoder connections
- Includes easily activated solid state relay, and local 24V transformer for PSR activation
- Easy wiring with labeled wire connections
- NEMA 3R enclosure with standard key lock

ELECTRICAL SPECIFICATIONS

- Primary AC Power: 120/230 VAC, 50/60 Hz, 50W
- Output (to PSR): 25V, 1600 mA
- MV Input: Dual pole, double throw solid state relay (10 A)



PSRB Pump Start Relay Booster

Height: 22 cm
Width: 18 cm
Depth: 9.5 cm

CONTROLLERS