



Sprayer: **BG Trailer**

Available Models: BG 600T, BG 800T, and BG 1000T

The **BG Trailer** series is designed specifically for orchards, nurseries, and vineyards where low horse power and compact tractors are a necessity. The poly tank is constructed from the highest quality material, ensuring impact resistance, UV stabilization, and a long chemical-resistant life. The BG series use A.R. pumps and controls which guarantee low maintenance and cost effective parts. The BG Trailer is a must for the professional grower.

Core Features:

- 164, 212, and 264 Gallon Poly Tank
- A.R. Diaphragm Pump
- VDR 50 Controller
- 28.5" Diameter Fan
- 12 Double Check Valve Nozzles
- Pressure Gauge and Control
- Recommended Tractor –35 hp to 40 hp









Sprayer: **BG Trailer**Available Models: **BG 600T, BG 800T, and BG 1000T**

	BG 600T	BG 800T	BG 1000T
Dry Weight	715 lbs	815 lbs	990 lbs
Length	108"	108"	119"
Width	41"	41"	51"
Height	48"	50"	54"
Capacity	164 Gallons	212 Gallons	264 Gallons
Pump			
Model	A.R. Diaphragm 1064	A.R. Diaphragm 1064	A.R. Diaphragm 1604
Power for Pump	13 hp	13 hp	13 hp
Controller	VDR 50	VDR 50	VDR 50
Nozzle Type	Teejet	Teejet	Teejet
Number of Nozzles	12	12	12
Nozzle Body Type	Braglia Double Nozzle w/ Check Valve	Braglia Double Nozzle w/ Check Valve	Braglia Double Nozzle w/ Check Valve
Electric Control			
Left/Right	Optional	Optional	Optional
Agitation	Hydro Venturi	Hydro Venturi	Hydro Venturi
Fan			
Diameter	28.5"	28.5"	28.5"
RPM	2100	2100	2100
Air Volume	21,612 cfm	21,612 cfm	21,612 cfm
Power	35 hp	35 hp	35 hp
Additional Equipment Specifications			
PTO Speed	540 rpm	540 rpm	540 rpm
Max Power	28 hp	28 hp	28 hp
Recommended Tractor Size	35 hp	40 hp	40 hp
Included Options			
Venturi Chemical Fill			
Galvanized Frame			
Quick Attach Fittings			
PTO Shaft			
			The National States
	THE RESERVE OF THE PARTY OF THE		