



VYRSA

VYR-35

Brass Sprinkler

3/4" Full Circle

Range: 40-60 feet

Flow: 3-14 gpm

The **VYR-35** is our flagship brass sprinkler. Compatible with almost any type of crop and a wide range of spacing conditions. It is a full circle sprinkler made with a combination of brass and stainless steel parts making it strong enough to withstand the weather and resist contact with the more aggressive fertilizers in the market.



FEATURES:

- Medium flow agricultural impact sprinkler
- 3/4" male connection
- Made of brass and stainless steel
- High-resistance rotating joints
- Nozzle angles of 26°
- Designed for full coverage irrigation
- Leading sprinkler in the agricultural market.

WaterTec

watertecna.com



1-877-591-4790



1-888-695-7999

Nozzle Size

PSI	1/8"		9/64"		5/32"		11/64"		3/16"		13/64"		7/32"	
	GPM	Feet	GPM	Feet	GPM	Feet	GPM	Feet	GPM	Feet	GPM	Feet	GPM	Feet
36	2.73	85	3.48	87	4.27	90	5.10	98	6.12	105	7.22	107	7.57	112
44	3.00	85	3.78	87	4.62	92	5.58	100	6.65	105	7.88	110	8.27	115
51	3.25	87	4.10	89	5.02	97	6.07	103	7.22	108	8.50	113	9.42	118
58	3.48	87	4.40	92	5.37	97	6.47	107	7.70	112	9.07	116	9.97	121
64	3.70	89	4.67	95	5.68	98	6.82	110	8.18	115	9.60	118	10.60	126
73	3.87	90	4.93	97	5.98	100	7.22	112	8.62	118	10.08	123	11.08	130
80	4.10	92	5.15	98	6.30	102	7.57	115	9.07	120	10.47	125	11.62	131



Height: 5.5"
Width: 6.7"
Weight: 0.95 lbs



The wide range of brass or plastic nozzles offer a number of possible combinations. This sprinkler is designed to work under a flow range between 3 and 14 gpm, at pressures between 25 and 65 PSI and a cover range between 42 and 60 feet of diameter. The **VYR-35** can work with one or two nozzles, both nozzles are 26 degree angle to the horizontal plane. Their average time of rotation comes to be approximately 40 sec.

