



FEATURES:

- 3-Point Hitch
- Manual Primer
- Suction Fitting
- Discharge Fitting
- Isolation Valve
- Pressure Gauge
- PTO Shaft

Model	RPM	Volume (GPM)															
		53		79		106		132		159		185		212		238	
		PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP
VG0-40/16	540	104	6.7	101	8	94	14	85	15	74	17	-	-	-	-	-	-
VG1-50/5	540	-	-	-	-	169	40	166	44	162	48	158	51	152	54	146	55
Model	RPM	Volume (GPM)															
		212		238		264		317		370		423		476		529	
		PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP
VG0-65/13	540	71	21	68	22	68	23	64	24	60	26	55	29	-	-	-	-
VG1-65/6	540	100	31	99	33	99	36	96	38	92	42	88	45	-	-	-	-
VG2-65/7	540	156	54	153	58	153	60	149	67	143	72	138	77	-	-	-	-
Model	RPM	Volume (GPM)															
		370		423		476		529		595		661		727		793	
		PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP	PSI	HP
VG2-80/8	540	104	51	103	55	102	60	99	62	97	67	92	71	88	74	-	-
VG3-80/9	540/1000	160	89	158	95	155	101	151	105	146	112	141	118	134	122	128	125
VG3-80/11	540/1000	125	64	124	68	122	72	121	77	118	82	114	87	109	89	107	92
VG4-80/9	540/1000	186	109	185	116	182	122	179	128	175	135	169	142	162	148	158	152