Maximum suggested horsepower

	Total width
F	Working width
6-3	Min. suggested horsepower
5 **	Weight
l. F	Maximum working depth
♥	Number of spades

90	HP	- 51	KV	V
	IN CM	IN CM	HP	I BS K

					8 -0			
	IN	СМ	IN	СМ	HP	LBS	KG	Nr.
150*	62	160	61	156	40	1653	750	6
165*	69	176	68	173	45	1687	765	6
180*	75	191	74	188	50	1940	880	8
200*	83	211	82	208	60	2028	920	8
220**	93	236	91	232	50	2204	1000	10
250**	103	262	102	259	50	2282	1035	10



Z90

SPADING MACHINE



THE IDEAL SOLUTION FOR:

- Eliminating ploughpan
- Reducing soil erosion
- Working in depth in narrow places
- Replacing the plough when working in difficult condi-tions.

TECHNICAL SPECIFICATIONS

- maximum horse power: 90 HP (44 KW)
- 4 speed gearbox for 540 rpm PTO
- oil bath lubrication and waterproof seal system
- 3 point hitch cat.1 from 150 up to 200; cat.2 from 220 up to 250
- rear tailgate with levelling flap
- working depth adjustment by skids
- spades: 225x175 mm (models 0180-200-220-250);
- 225x205 mm (models 165)drive shaft with clutch
- safety protections

* Machines supplied as standard with low PTO gearbox (suitable for tractors with PTO height up to 65 cm)

** Machines supplied as standard with high PTO gearbox (suitable for tractors with PTO height from 65 to 85 cm)