



www.celli-usa.com  
Toll Free: 1-877-591-4790

# MAXI

MAXI														
	IN	CM	IN	CM	HP / KW	LBS	KG	LBS	KG	LBS	KG	LBS	KG	Nr.
300	120	305	118	300	140/102	2910	1320	2910	1320	3285	1490	2976	1350	24
350	140	355	138	350	160/117	3197	1450	3197	1450	3615	1640	3262	1480	28
400	159	405	157	400	180/131	3483	1580	3483	1580	3946	1790	3549	1610	32
450	179	455	177	450	200/146	3770	1710	3770	1710	4277	1940	3836	1740	36

	Total width		Weight with spikes roller		Weight with spiral roller		Min. suggested horsepower
	Working width		Weight with packer roller		N° of blades		Weight with cage roller

## FIXED POWER HARROW



**MAXI is the top power harrow in the Celli range and is suitable to tractors up to 250 HP maximum.**

### POINTS OF STRENGTH:

- Well proportioned, high quality transmission components (thick one-piece rotors and hardened gears kept together by strong self-locking nuts);
- Completely redesigned bottom area in order to make it more resistant to wearing and improve the soil flow through the machine (double lips oil seals + external protecting groove; bottom housings made of forged steel);
- Innovative bottom stone guards (L-shaped thick plates welded onto the frame + complete bolted cover).

### TECHNICAL SPECIFICATIONS

- maximum horse power: 250 HP (183 KW)
- 2 speed gearbox for 1000 rpm PTO
  - No. of teeth models 300-400
    - 25 - 14 = 323 rpm;
    - 24 - 15 = 360 rpm
  - No. of teeth models 350-450
    - 14 - 25 = 323 rpm
    - 15 - 24 = 360 rpm
- 3 point hitch cat.2
- swinging lower linkages
- rear roller adjustment by hydraulic system
- rear levelling bar adjustment by threaded bar
- round tines holder kit to avoid jamming
- tines 100x18x320 mm (working depth about 33 cm) low power absorption
- counter-plates for tines locking
- movable side plates
- drive shaft with cam clutch
- removable safety protections